

**FUGRO TECHNICAL SERVICES LIMITED**

MaterialLab Division,  
Fugro Development Centre,  
5 Lok Yi Street, 17 M.S. Castle Peak Road,  
Tai Lam, Tuen Mun, N.T., Hong Kong.

Tel : +852-2450 8233  
Fax : +852-2450 6138  
E-mail : matlab@fugro.com.hk  
Website : www.materiallab.com.hk

**MaterialLab**

Client Ref. : --

Report No. : 075231CN90033(1)

Page 1 of 1

**REPORT ON WATER PERMEABILITY TEST****Information Supplied by Client**

Client : Master Proofer Company Limited  
Project : Material Testing  
Sample Description : Ø100mm Concrete Core with Construction Joint coated with  
Coral Flexible W889 and Labond A907 Net Mesh (Thickness 2.5mm)  
Client Sample I.D. : --  
Location of Drilled Core : 50mm thick concrete panel with construction joint (Concrete grade 25/20)

**Laboratory Information**

Lab. Sample I.D. : CN90033/2  
Sample Received : 15 January 2009  
Date Test Started : 05 February 2009  
Date Test Completed : 17 March 2009  
Diameter of Sample : 0.1001 m  
Thickness of Sample (L) : 0.0518 m  
Cross-Sectional Area (A) : 0.0079 m<sup>2</sup>  
Test Method : In accordance with our in-house method ref. : CNMS-072

**Test Results**

Testing Pressure (bar)	Pressure Direction	Water Permeation of Sample	Coefficient of Permeability (m/s)
4.5	Front	No	#

Remark : # The specimen was inspected and no watermark or seepage was found.

Checked by: [Signature] Date: 6/4/09 Certified by: [Signature] Date: 6-4-09  
Wong Tin Woon

**FUGRO TECHNICAL SERVICES LIMITED**

MaterialLab Division,  
Fugro Development Centre,  
5 Lok Yi Street, 17 M.S. Castle Peak Road,  
Tai Lam, Tuen Mun, N.T., Hong Kong.

Tel : +852-2450 8233  
Fax : +852-2450 6138  
E-mail : matlab@fugro.com.hk  
Website : www.materiallab.com.hk

**MaterialLab**

Client Ref. : --

Report No. : 075231CN90033

Page 1 of 1

**REPORT ON WATER PERMEABILITY TEST****Information Supplied by Client**

Client : Master Proofer Company Limited  
Project : Material Testing  
Sample Description : Ø100mm Concrete Core with Construction Joint coated with  
Coral Flexible W889 (Thickness 2mm)  
Client Sample I.D. : --  
Location of Drilled Core : 50mm thick concrete panel with construction joint (Concrete grade 25/20)

**Laboratory Information**

Lab. Sample I.D. : CN90033/1  
Sample Received : 15 January 2009  
Date Test Started : 05 February 2009  
Date Test Completed : 12 February 2009  
Diameter of Sample : 0.1001 m  
Thickness of Sample (L) : 0.0513 m  
Cross-Sectional Area (A) : 0.0079 m<sup>2</sup>  
Test Method : In accordance with our in-house method ref. : CNMS-072

**Test Results**

Testing Pressure (bar)	Pressure Direction	Water Permeation of Sample	Coefficient of Permeability (m/s)
0.6	Front	No	#

Remark : # The specimen was inspected and no watermark or seepage was found.

Checked by: J. Cate Date: 6/4/09 Certified by: Wong Tin Woon Date: 6-4-09

## FUGRO TECHNICAL SERVICES LIMITED

MaterialLab Division,  
Fugro Development Centre,  
5 Lok Yi Street, 17 M.S. Castle Peak Road,  
Tai Lam, Tuen Mun, N.T., Hong Kong.

Tel : +852-2450 8233  
Fax : +852-2450 6138  
E-mail : matlab@fugro.com.hk  
Website : www.fugro.com

# MaterialLab

Report No. : 040123RM40106(2)

Page 1 of 1

Client's Ref. : --

### REPORT ON FLEXURAL STRENGTH OF MORTAR

Client : Master Proofer Company Limited

Project : Material Testing

Location : --

W/I No. : --

Sample Description : - Type : Labond Coral W889 Flexible Cementitious Waterproofing Coating  
Source : --  
Batch No. : --

Batch ID : RM40106

Nominal Dimension of Specimen : 25 x 25 x 100 mm

Method of Compaction : By hand

Curing Regime : 27 ± 2 °C, 55 ± 5% RH

Location of Sampling : Concrete Lab. of MaterialLab

Date Cast : 24-Apr-2004

Date Received : 16-Mar-2004

Date Tested : 22-May-2004

Age at Test : 28 days

Test Method : BS 6319 : Part 3 : 1983 (with modification see remark 1)

### Test Result

Specimen Identification	Dimensions of Failure Area (mm)	Mass of Specimen (g)	Maximum Load (N)	Flexural Strength (N/mm <sup>2</sup> )
RM40106/1D	24.4 x 23.8	100.4	355	2.8
RM40106/1E	24.5 x 24.1	101.3	363	2.8
RM40106/1F	24.5 x 24.3	101.2	378	3.0
			Mean	2.8

Remark : (1) The three test specimens instead of four specimens were tested.

Checked by : mlb Certified by : M. Q. Su Date : 7-6-2004  
(Felix Chan/M.Q. Su/T.K. Cheung)

## FUGRO TECHNICAL SERVICES LIMITED

MaterialLab Division,  
Fugro Development Centre,  
5 Lok Yi Street, 17 M.S. Castle Peak Road,  
Tai Lam, Tuen Mun, N.T., Hong Kong.

Tel : +852-2450 8233  
Fax : +852-2450 6138  
E-mail : matlab@fugro.com.hk  
Website : www.fugro.com

# MaterialLab

Report No. : 040123RM40106(3)

Page 3 of 3

### Report on Pull-off Test

Test method used : In-house Method Based on HKHA/MTS (02/04) Specification, Part D,  
Clause 2.1.15 (Method 1)

### Information Supplied by Client

Client : Master Proofer Company Limited

Project : Material Testing

Location : --

Client sample ID : --

Type of the testing material : Labond Coral W889 Flexible Cementitious Waterproofing Coating Class : --

Age of the testing material at the time of pull-off test : 28 days

### Laboratory Information

Description of pull-off tester : Dyna Z15

Description of dolly : Aluminium Dolly of 75 mm Diameter x 30 mm Thickness

Type of adhesive : Fast-set 4 Minutes Clear Epoxy

Date of testing : 22-May-2004

Tested by : T.W. Wong

### Test Results

Laboratory sample ID : RM40106/3C

Measured Core diameter at the rupture face (mm) : 74.4

Core length after pull-off test (mm) : Max.: 2.0 Min.: 2.0

Thickness of the testing material after pull-off test (mm) : Max.: 2.0 Min.: 2.0

Failure load, F (N) : 3200

Bond strength (N/mm<sup>2</sup>) : 0.7

Type of failure : 100% of failure plane was mortar failure.

Remark : The accuracy of the pull-off tester is within  $\pm 4$  % of the measured load in the range from  
1.2 kN to 16 kN.

Checked by : M6 Date : 7-6-04 Certified by : (Signature) Date : 7-6-2004  
(M.Q. Su / T.K. Cheung)





香港標準及檢定中心  
Hong Kong Standards and Testing Centre

Date : 2004-05-14  
No. : HC151168

**TEST REPORT**

Page 1 of 2

**Applicant(Code:MAP007)** : Master Proofer Co Ltd  
Unit I 8/F On Ho Ind Bldg  
17-19 Shing Wan Rd  
Tai Wai NT

**Description of Samples** : One submitted sample said to be Labond Coral Flexible W889  
Flexible cementitious waterproofing coating.  
Reference No.: W889  
Country of Origin: HK

**Date Samples Received** : 2004-05-03

**Date Tested** : 2004-05-12 to 2004-05-13

**Investigation Requested** : BS 6920: Part 1: 1996: Clause 8: The extraction of metals  
Suitability of non-metallic products for use in contact with water  
intended for human consumption with regard to their effect on the  
quality of the water BS 6920: Part 1: 1996: Clause 8: The  
extraction of metals

**Conclusions** : The test results of the submitted sample **complied** with the  
specifications of BS 6920: Part 1: 1996: Clause 8: The extraction of  
metals.

  
Anne Chuah, CFD  
For Chief Executive



This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.



香港標準及檢定中心  
Hong Kong Standards and Testing Centre

Date : 2004-05-14  
No. : HC151168

**TEST REPORT**

Page 2 of 2

**Method(s) Used:**

BS 6920: Part 1: 1996 and BS 6920: Section 2.6: 1996

**Test Results:**

Test Item(s)	Results ( $\mu\text{g/L}$ )	Max. allowable concentration# ( $\mu\text{g/L}$ )
1. Aluminium	<100	200
2. Antimony	<10	10
3. Arsenic	<10	50
4. Barium	<100	1000
5. Cadmium	<5	5
6. Chromium	<10	50
7. Iron	<100	200
8. Lead	<10	50
9. Manganese	<10	50
10. Mercury	<1	1
11. Nickel	<10	50
12. Selenium	<10	10
13. Silver	<10	10

Notes: # quoted from Table 1 of BS 6920: Part 1: 1996  
< denotes less than  
 $\mu\text{g/L}$  denotes microgram per Litre

\*\*\*\*\* End of Test Report \*\*\*\*\*