



# Thanetop F769

## Foot Traction Top Coat 雙組份防滑聚胺脂面漆

### 1.0 Description

Thanetop F769 is specially formulation Solvent free MDI Polyurethane coating system intended for overcoating onto traditional waterproofing as non-slipping, non-sticky, foot-abrasion topping. It is also a non-dust attractive finish which is suitable for both exterior and interior area.

### 2.0 Technical Data

Product	F769	F769
Items	Part A	Part B
Appearance	Yellowish liquid	Colored liquid
Viscosity (cps. 25°C)	200 ± 50	1,000 ± 10
Mixing ratio (w/w)	1	3
Sp.gr	1.4 ± 0.05	
Pot-life (min)	30 – 60	
Tensile strength (Kgf/cm <sup>2</sup> )	150 – 250	
Elongation (%)	70 – 80	
Hardness (Shore A)	85	

### 3.0 Application

Thanetop F769 is a two component product; do not mix any thinner or other additive. Once it is open, apply it by bush within 30 minutes in one to two coating subject to underneath substrate condition.

### 4.0 Packaging

4 Kg/Set (Part A: 3Kg; Part B:1Kg)

16 Kg/Set (Part A: 12Kg; Part B: 4Kg)

### 5.0 Technical Service

The Marketing and Technical offices of Master Proofer Company Ltd are readily available for advice on any of the Company's products.

