



# MetalGuard P942

## Anti-Corrosion Primer for Concrete and Metal

抗銹蝕底油(三合土及鐵器用)

### 1.0 DESCRIPTION

MetalGuard P942 is a solvent based acrylic primer for concrete, masonry or metal surface prior to laying paint or waterproofing membrane.

#### Uses

- To act as protective primer to metal from rusting.
- To seal and prepare concrete or masonry surfaces for waterproofing

### 2.0 TECHNICAL DATA

Colour	Greenish
Specific Gravity	0.92
Drying Time	15-30 mins.
VOC Content	296 g/L

### 3.0 APPLICATION

Apply directly from the pail. Ensure a clear sheen after application and allow to dry before applying additional paint or waterproofing membrane. Drying time is approximately 15 – 30 minutes depending on temperature and substrate condition.

### 4.0 SHELF LIFE

Up to 12 months in an unopened container, stored in a cool dry place.

### 5.0 HEALTH AND SAFETY

This product contains solvent and is flammable. Do not use near naked flame or smoke during handling. Wear protective gloves and safety goggles. Avoid excessive inhalation. In case of skin contact or accidental eye contamination, wash with plenty of clean water.

### 6.0 PACKING AND COVERAGE

Approximately 10-15m<sup>2</sup> per litre depending on the substrate condition.  
1 Litre/Can and 5 Litres/Can

LABOND